




SUPPORTI SERIE K  
HOUSING SERIE K  
SOFT



Caratteristiche supporti

Wheel centre:  
Polypropylene, Tread:  
Polyurethane, foamed,  
precision ball bearing,  
temperature range  
from - 20 to + 60 °C



girevole foro per vite  
freno totale  
girevole foro per vite  
freno direzionale

bolt hole castor

bolt hole castor total lock

bolt hole castor directional lock

|        |    |    |     |
|--------|----|----|-----|
| 100x32 | 12 | 44 | 150 |
| 125x32 | 12 | 45 | 175 |

|     |                      |
|-----|----------------------|
| 90  | K1 2100 Q12 SOFT GIB |
| 100 | K1 2125 Q12 SOFT GIB |



Technical Data

|                        |                |
|------------------------|----------------|
| Wheel diameter         | 100 mm         |
| Width of Tread         | 30 mm          |
| Axle Hole-Ø            | 8 mm           |
| Hub length             | 36.5 mm        |
| Temperature            | - 20 / + 60 °C |
| Standard               | EN 12530       |
| Weight                 | 0.14 kg        |
| Hardness of tread      | Shore A 70     |
| Load capacity          | 60 kg          |
| Load capacity (static) | 120 kg         |

Technische Daten

|                          |                |
|--------------------------|----------------|
| Rad-Ø                    | 125 mm         |
| Radbreite                | 30 mm          |
| Achslloch-Ø              | 8 mm           |
| Nabenlänge               | 36.5 mm        |
| Temperaturbereich        | - 20 / + 60 °C |
| Norm                     | EN 12530       |
| Eigengewicht             | 0.212 kg       |
| Härte der Lauffläche     | Shore A 70     |
| Tragfähigkeit            | 75 kg          |
| Tragfähigkeit (statisch) | 150 kg         |

Varianti/Options

Kolo namenjeno za servirne vozičke.  
Z mehko visoko penasto gumo.



Technical Data

|                        |                |
|------------------------|----------------|
| Wheel diameter         | 100 mm         |
| Width of Tread         | 30 mm          |
| Axle Hole-Ø            | 8 mm           |
| Hub length             | 36.5 mm        |
| Temperature            | - 20 / + 60 °C |
| Standard               | EN 12530       |
| Weight                 | 0.14 kg        |
| Hardness of tread      | Shore A 70     |
| Load capacity          | 60 kg          |
| Load capacity (static) | 120 kg         |

Technische Daten

|                          |                |
|--------------------------|----------------|
| Rad-Ø                    | 125 mm         |
| Radbreite                | 30 mm          |
| Achslloch-Ø              | 8 mm           |
| Nabenlänge               | 36.5 mm        |
| Temperaturbereich        | - 20 / + 60 °C |
| Norm                     | EN 12530       |
| Eigengewicht             | 0.212 kg       |
| Härte der Lauffläche     | Shore A 70     |
| Tragfähigkeit            | 75 kg          |
| Tragfähigkeit (statisch) | 150 kg         |

Le dimensioni riportate sulle pagine del nostro catalogo sono espresse in millimetri  
All dimensional sizes shown on our catalogue are in millimeters.