



RUOTE NUCLEO ACCIAIO STAMPATO ANELLO GOMMA NERA O GRIGIA STANDARD

PRESSED STEEL CENTRE WHEELS WITH BLACK OR GREY STANDARD RUBBER TYRE



Caratteristiche Ruota

Anello in gomma nera qualità standard. **LN**
Anello in gomma grigia antitraccia. **LG**
Anello in gomma grigia ELASTICA antitraccia. **LQ**
Struttura portante composta da doppi dischi acciaio stampato zincati galvanicamente assemblati con rivetti alluminio.
Movimento mozzo:
boccola poliammide autolubrificante.
gabbia a rulli.
Temperatura d'impiego da -10°C a +60°C.
Discreta resistenza agli aggressivi chimici.
Durezza battistrada 83 Sh.A +/- 4
Discreta resistenza all'abrasione
Velocità massima di lavoro 4 km/h.
Mezzo di trazione consigliato: manuale

Wheel Features

Black standard rubber tyre. **LN**
Grey non-marking rubber tyre. **LG**
Grey non-marking ELASTIC rubber tyre. **LQ**
Pressed steel zinc-plated rivetted rims.
Type of bearing:
self-lubricating polyamide bush.
roller bearing.
Temperature range: from -10°C to +60°C.
Fair resistance to chemicals.
Tread hardness 83 Sh.A +/- 4
Fair resistance to abrasion.
Max. working speed 4 KPH.
Operation: manual.

Pavimentazioni Idonee / Floring Type



	COD		
80x25	OLNR080012	12x40	50
100x30	OLNR100012	12x40	70
125x37,5	OLNR125015	15x46	100
140x37,5	OLNR140015	15x46	115
150x40	OLNR150015	15x46	125
160x40	OLNR160020	20x60	135
180x45	OLNR180020	20x60	170
200x50	OLNR200020	20x60	205
250x60	OLNR250025	25x75	295
250x60	OLNR250A25	25x60	295
280x70	OLNR280025	25x75	385
80x25	OLGR080012	12x40	50
100x30	OLGR100012	12x40	70
125x37,5	OLGR125015	15x46	100
150x40	OLGR150015	15x46	125
160x40	OLGR160020	20x60	135
200x50	OLQR200020	20x60	205

Varianti / Options



Parafili in acciaio stampato
Steel thread guards

Le dimensioni riportate sulle pagine del nostro catalogo sono espresse in millimetri
All dimensional sizes shown on our catalogue are in millimeters.