

RUOTE NUCLEO POLIAMMIDE ANELLO GOMMA BLU O GRIGIA ELASTICA
ANTITRACCIA

POLYAMIDE CENTRE WHEELS WITH BLUE OR GREY NON-MARKING
ELASTIC RUBBER TYRES



Caratteristiche Ruota

Anello gomma blu ELASTICA antitraccia **NG**
Anello gomma grigia ELASTICA antitraccia **NH**
Struttura portante in poliammide colore nero.
Movimento mozzo:
gabbia a rulli.
gabbia a rulli con pista di scorrimento in acciaio.
doppi cuscinetti a sfera tenuta stagna.
Temperatura d'impiego da -10°C a $+60^{\circ}\text{C}$.
Buona resistenza agli aggressivi chimici.
Durezza battistrada 65 Sh.A +/- 5.
Ottima resistenza all'abrasione.
Velocità massima di lavoro 4 km/h.
Mezzo di trazione consigliato: manuale.

Wheel Features

Blue non-marking ELASTIC rubber tyre **NG**
Grey non-marking ELASTIC rubber tyre **NH**
Black polyamide centre wheel.
Type of bearing:
roller bearing.
roller bearing with steel tube.
double waterproof ball bearings
Temperature range: from -10°C to $+60^{\circ}\text{C}$.
Good resistance to chemicals.
Tread hardness 65 Sh.A +/- 5.
Very good resistance to abrasion.
Max. working speed 4 KPH.
Operation: manual.

Pavimentazioni Idonee / Floring Type



100x32	ONGR100S12	12x40	160				
100x38				ONGE100L15	15x46	200	
125x40				ONGE125L15	15x46	225	ONGT125L15 15x47 30 225
160x50				ONGE160L20	20x60	300	ONGT160L20 20x61 40 300
200x50				ONGE200020	20x60	400	ONGT200020 20x61 40 400
100x32	ONHX100S12	12x40	160				
100x38	ONHX100L15	15x46	200				
125x40	ONHX125L15	15x46	225				ONHT125L15 15x47 30 225
160x50	ONHX160L20	20x60	300				ONHT160L20 20x61 40 300
200x50	ONHX200020	20x60	350				ONHT200020 20x61 40 400

Varianti / Options



MN Anello in gomma grigia elastica antistatica
Antistatic elastic grey rubber tyre



Parafili in lega leggera
Light Metal thread guards



Parafili in poliammide
Polyamide thread guards

Le dimensioni riportate sulle pagine del
nostro catalogo sono espresse in millimetri
All dimensional sizes shown on our
catalogue are in millimeters.