

RUOTE NUCLEO POLIAMMIDE ANELLO GOMMA BLU O GRIGIA ELASTICA ANTITRACCIA

POLYAMIDE CENTRE WHEELS WITH BLUE OR GREY NON-MARKING ELASTIC RUBBER TYRES




Caratteristiche Ruota

- Anello in gomma blu ELASTICA antitraccia**NG**
- Anello in gomma grigia ELASTICA antitraccia**NH**
- Struttura portante in poliammide colore nero.
- Movimento mozzo: gabbia a rulli.
- gabbia a rulli con pista di scorrimento in acciaio.
- doppi cuscinetti a sfera tenuta stagna.
- Temperatura d'impiego da -10°C a +60°C.
- Buona resistenza agli aggressivi chimici.
- Durezza battistrada 65 Sh.A +/- 5.
- Ottima resistenza all'abrasione.
- Velocità massima di lavoro 4 km/h.
- Mezzo di trazione consigliato: manuale.

Wheel features

- Blue non-marking ELASTIC rubber tyre.**NG**
- Grey non-marking ELASTIC rubber tyre.**NH**
- Black polyamide centre wheel.
- Type of bearing: roller bearing.
- roller bearing with steel tube.
- double waterproof ball bearings
- Temperature range: from -10°C to +60°C.
- Good resistance to chemicals.
- Tread hardness 65 Sh.A +/- 5.
- Very good resistance to abrasion.
- Max. working speed 4 KPH.
- Operation: manual.

Modalità di impiego/Main features



100x30	ONGR100A12	12x40	160				
100x38				ONGE100L15	15x46	200	
125x40				ONGE125L15	15x46	225	ONGT125L15 15x47 30 225
160x45				ONGE160020	20x60	300	ONGT160020 20x61 40 300
200x50				ONGE200020	20x60	400	ONGT200020 20x61 40 400
100x30	ONHX100A12	12x40	160				
100x38				ONHW100L15	15x46	200	
125x40				ONHW125L15	15x46	225	ONHT125L15 15x47 30 225
160x45				ONHW160020	20x60	300	ONHT160020 20x61 40 300
200x50				ONHW200020	20x60	350	ONHT200020 20x61 40 400

Varianti/Options

Accessori/Accessories



Parafili in lega leggera
Light Metal thread guards



Parafili in poliammide
Polyamide thread guards