



Tel: 04/257 68 20
Gsm: 040/99 00 11

RUOTE IN ALLUMINIO PRESSOFUSO ANELLO GOMMA NERA O GRIGIA
ELASTICA VULCANIZZATO

ALUMINIUM CENTRE WHEELS WITH BLACK OR GREY ELASTIC
VULCANIZED RUBBER TYRES



Caratteristiche Ruota

Anello gomma "ELASTICA" vulcanizzata:
ZV colore nero **ZF** colore grigio
Struttura portante in alluminio pressofuso
Mozzo cuscinetti a sfere tenuta stagna.
Temperatura d'impiego da -15°C a +60°C.
Discreta resistenza agli aggressivi chimici.
Durezza battistrada 70 Sh.A +/- 5
Ottima resistenza all'abrasione.
Velocità massima di lavoro 4 km/h.
Mezzo di trazione consigliato:
manuale-meccanico.

Wheel Features

Black "ELASTIC" vulcanized rubber tyre.**ZV**
Grey "ELASTIC" vulcanized rubber tyre.**ZF**
Die-cast aluminium centre wheel.
Type of bearing:
double waterproof ball bearings
Temperature range: from -15°C to +60°C.
Fair resistance to chemicals.
Tread hardness 70 Sh.A +/- 5.
Very good resistance to abrasion.
Max. working speed 4 KPH.
Operation: manual-mechanical.

Pavimentazioni Idonee / Floring Type



100x40	OZVT100015	15x47	30	150
125x50	OZVT125020	20x61	50	225
160x40	OZVT160A12	12x61	56	300
160x50	OZVT160020	20x61	50	300
180x50	OZVT180020	20x61	50	350
200x50	OZVT200020	20x61	50	400
200x50	OZVT200A25	25x61	50	400
250x50	OZVT250025	25x61	50	500
300x60	OZVT300A30	30x60	60	700
100x40	OZFT100015	15x47	30	150
125x50	OZFT125020	20x61	50	225
160x40	OZFT160A12	12x61	56	300
160x50	OZFT160020	20x61	50	300
180x50	OZFT180020	20x61	50	350
200x50	OZFT200020	20x61	50	400
200x50	OZFT200A25	25x61	50	400
250x50	OZFT250025	25x61	50	500

Varianti / Options



ZN Anello in gomma grigia Elastica conduttiva
Conductive elastic grey rubber tyre

Le dimensioni riportate sulle pagine del
nostro catalogo sono espresse in millimetri
All dimensional sizes shown on our
catalogue are in millimeters.