

RUOTE IN ALLUMINIO PRESSOFUSO ANELLO GOMMA NERA O GRIGIA ELASTICA VULCANIZZATO

ALUMINIUM CENTRE WHEELS WITH BLACK OR GREY ELASTIC VULCANIZED RUBBER TYRES




Caratteristiche Ruota

- Anello in gomma nera "ELASTICA" vulcanizzato. **ZV**
- Anello in gomma grigia "ELASTICA" vulcanizzato. **ZF**
- Struttura portante in alluminio pressofuso
- Movimento mozzo: doppi cuscinetti a sfere tenuta stagna.
- Temperatura d'impiego da -15°C a +60°C.
- Discreta resistenza agli aggressivi chimici.
- Durezza battistrada 70 Sh.A +/- 5
- Ottima resistenza all'abrasione.
- Velocità massima di lavoro 4 km/h.
- Mezzo di trazione consigliato: manuale-meccanico.

Wheel features

- Black "ELASTIC" vulcanized rubber tyre. **ZV**
- Grey "ELASTIC" vulcanized rubber tyre. **ZF**
- Die-cast aluminium centre wheel.
- Type of bearing: double waterproof ball bearings
- Temperature range: from -15°C to +60°C.
- Fair resistance to chemicals.
- Tread hardness 70 Sh.A +/- 5.
- Very good resistance to abrasion.
- Max. working speed 4 KPH.
- Operation: manual-mechanical.

Modalità di impiego/Main features



100x40	OZVT100015	15x47	30	150	OZVL100035B	35x14-36
125x50	OZVT125020	20x61	50	225	OZVL125047D	47x17,5-57
125x50					OZVL125A47A	47x12,5-54
160x50	OZVT160020	20x61	50	300	OZVL160047D	47x17,5-57
160x50					OZVL160A47A	47x12,5-54
180x50	OZVT180020	20x61	50	350	OZVL180047D	47x17,5-57
200x50	OZVT200020	20x61	50	400	OZVL200047D	47x17,5-57
200x50	OZVT200A25	25x61	50	400	OZVL200A52B	52x18,5-57
200x50					OZVL200B47A	47x12,5-54
250x50	OZVT250025	25x61	50	500	OZVL250052B	52x18,5-57
250x50					OZVL250A47A	47x12,5-54
300x60	OZVT300A30	30x60	60	700	OZVL300A62A	62x16-60
100x40	OZFT100015	15x47	30	150	OZFL100035B	35x14-36
125x50	OZFT125020	20x61	50	225	OZFL125047D	47x17,5-57
160x50	OZFT160020	20x61	50	300	OZFL160047D	47x17,5-57
180x50					OZFL180047D	47x17,5-57
200x50	OZFT200020	20x61	50	400	OZFL200047D	47x17,5-57
200x50					OZFL200A52B	52x18,5-57
250x50					OZFL250052B	52x18,5-57

Varianti/Options



Anello in gomma grigia Elastica conduttiva
Conductive elastic grey rubber tyre

Accessori/Accessories