

RUOTE IN GHISA MECCANICA ANELLO GOMMA NERA CALETTATO
CONTINENTAL ELASTIC

CAST IRON WHEELS WITH BLACK CONTINENTAL ELASTIC RUBBER
TYRES

Caratteristiche Ruota

Anello in gomma nera "CONTINENTAL ELASTIC"

calettato a due durezza e parte interna con cavi in acciaio per la tenuta dell'anello sul nucleo portante.

Struttura portante in ghisa meccanica.

Movimento mozzo:

doppi cuscinetti a sfere tenuta stagna.

Temperatura d'impiego da -15°C a +60°C.

Discreta resistenza agli aggressivi chimici.

Durezza battistrada 70 Sh.A +/- 5

Ottima resistenza all'abrasione.

Velocità massima di lavoro 4 km/h.

Mezzo di trazione consigliato:

manuale-meccanico.

Wheel Features

Black "CONTINENTAL ELASTIC" rubber tyre fitted with wires on the centre wheel core.

Cast iron centre wheel.

Type of bearing:

double waterproof ball bearings

Temperature range: from -15°C to +60°C.

Fair resistance to chemicals.

Tread hardness 70 Sh.A +/- 5.

Very good resistance to abrasion.

Max. working speed 4 KPH.

Traction system: manual-mechanical.



Pavimentazioni Idonee / Floring Type



| Dimensione | COD | Ø | h | W |
|------------|------------|-------|----|------|
| 125x50 | ORGT125020 | 20x61 | 50 | 225 |
| 150x50 | ORGT150020 | 20x61 | 50 | 250 |
| 160x50 | ORGT160020 | 20x61 | 50 | 300 |
| 180x50 | ORGT180020 | 20x61 | 50 | 350 |
| 200x50 | ORGT200025 | 25x61 | 50 | 400 |
| 200x75 | ORGT200A25 | 25x90 | 69 | 600 |
| 230x50 | ORGT230025 | 25x61 | 50 | 500 |
| 230x75 | ORGT230A30 | 30x90 | 67 | 650 |
| 250x50 | ORGT250025 | 25x61 | 50 | 500 |
| 250x60 | ORGT250A25 | 25x76 | 55 | 600 |
| 250x80 | ORGT250B30 | 30x90 | 67 | 675 |
| 280x75 | ORGT280030 | 30x90 | 67 | 700 |
| 300x85 | ORGT300A35 | 35x90 | 90 | 800 |
| 400x75 | ORGT400035 | 35x90 | 90 | 1000 |

Varianti / Options

Le dimensioni riportate sulle pagine del nostro catalogo sono espresse in millimetri
All dimensional sizes shown on our catalogue are in millimeters.