

**RUOTA / WHEEL**Gres/  
StonewareAsfalto/  
AsphaltGrigliato/  
GridCemento/  
Concrete**18AS / AVOANTISTATIC 91 Shore A****18AS**

Ruota in poliuretano antistatico,  
nucleo in alluminio  
*Antistatic polyurethane wheel  
tread and aluminium centre*



105 ÷ 700



-20 ÷ +80



Ruota con rivestimento  
in poliuretano  
AVOANTISTATIC  
antistatico 91 Shore A.  
Nucleo in alluminio.  
Mozzo a cuscinetti  
a sfere schermati  
assemblati con  
distanziale centrale.

*Wheel coated  
with antistatic  
AVOANTISTATIC  
polyurethane tread  
91 Shore A.  
Wheel centre in  
aluminium. Hub on  
shielded ball bearings  
assembled with  
central spacer.*

Le caratteristiche elettriche di resistenza che vengono garantite dal materiale e dal processo produttivo, sono sintetizzabili dalla disuguaglianza:  
 $R \leq 50$  Mega Ohm.

*The measured electrical characteristics that are guaranteed by the material and production, process can be summarized by the inequality:  
 $R \leq 50$  Mega Ohm.*

La ruota 18AS può essere assemblata con tutti i tipi di supporti medio e pesante.  
*The wheel 18AS can be assembled with all medium and heavy duty castors.*

<b>80x25</b>	30	12	32x10	105
<b>80x30</b>	40	12	32x10	126
<b>100x30</b>	30	15	35x11	140
<b>100x40</b>	40	12	32x10	175
<b>100x50</b>	60	20	47x14	280
<b>125x30</b>	30	15	35x11	175
<b>125x40</b>	50	20	47x14	210
<b>125x50</b>	60	20	47x14	259
<b>150x40</b>	40	20	47x14	280
<b>160x50</b>	60	20	47x14	350
<b>160x50</b>	60	25	52x15	350
<b>175x50</b>	60	20	47x14	420
<b>180x50</b>	60	20	47x14	490
<b>200x50</b>	60	20-25	47x14	560
<b>250x50</b>	60	30	62x16	700