

## RUOTA / WHEEL



Gres/  
Stoneware



Asfalto/  
Asphalt



Grigliato/  
Grid



Cemento/  
Concrete



18AS / AVOANTISTATIC 91 Shore A

# 18AS

Ruota in poliuretano antistatico,  
nucleo in alluminio  
*Antistatic polyurethane wheel  
tread and aluminium centre*



105 ÷ 700



-20 ÷ +80








Ruota con rivestimento  
in poliuretano  
AVOANTISTATIC  
antistatico 91 Shore A.  
Nucleo in alluminio.  
Mozzo a cuscinetti  
a sfere schermati  
assemblati con  
distanziale centrale.

*Wheel coated  
with antistatic  
AVOANTISTATIC  
polyurethane tread  
91 Shore A.  
Wheel centre in  
aluminium. Hub on  
shielded ball bearings  
assembled with  
central spacer.*

Le caratteristiche elettriche di resistenza che vengono garantite dal materiale e dal processo produttivo, sono sintetizzabili dalla disuguaglianza:  
 $R \leq 50$  Mega Ohm.

*The measured electrical characteristics that are guaranteed by the material and production, process can be summarized by the inequality:  
 $R \leq 50$  Mega Ohm.*

La ruota 18AS può essere assemblata con tutti i tipi di supporti medio e pesante.  
*The wheel 18AS can be assembled with all medium and heavy duty castors.*

				
80x25	30	12	32x10	105
80x30	40	12	32x10	126
100x30	30	15	35x11	140
100x40	40	12	32x10	175
100x50	60	20	47x14	280
125x30	30	15	35x11	175
125x40	50	20	47x14	210
125x50	60	20	47x14	259
150x40	40	20	47x14	280
160x50	60	20	47x14	350
160x50	60	25	52x15	350
175x50	60	20	47x14	420
180x50	60	20	47x14	490
200x50	60	20-25	47x14	560
250x50	60	30	62x16	700