



### RUOTE A STRUTTURA MONOLITICA IN POLIAMMIDE POLYAMIDE WHEELS

#### Caratteristiche Ruota


Struttura portante in poliammide 6 ad alta densità  
Movimento mozzo: alesaggio passante.  
gabbia a rulli.  
gabbia a rulli con pista di scorrimento in acciaio.  
doppi cuscinetti a tenuta stagna.  
Temperatura d'impiego da -15°C a +80°C.  
Buona resistenza agli aggressivi chimici.  
Buona resistenza all'abrasione.  
Velocità massima di lavoro 4 km/h.  
Mezzo di trazione consigliato: manuale.

#### Wheel Features

High density polyamide 6 wheel.  
Type of bearing:  
plain bearing.  
roller bearing.  
roller bearing with steel tube.  
double waterproof ball bearings.  
Temperature range: from -15°C to +80°C.  
Good resistance to chemicals.  
Good resistance to abrasion.  
Max. working speed 4 KPH.  
Operation: manual.



#### Pavimentazioni Idonee / Floring Type



80x30	COD	12x40	150	COD	12x40	150	80x35	COD	12x40	200			
	ONNA080012			ONNR080012				ONNE080A12					
100x35	ONNA100012	12x40	200	ONNR100012	12x40	200							
100x40	ONNA100A15	15x46	250				ONNE100A15	15x46	250				
100x45	ONNA100B20	20x60	350				ONNE100B20	20x60	350	ONNT100B20	20x61	40	400
100x50										ONNT100C20	20x61	50	600
125x40	ONNA125015	15x46	300	ONNR125015	15x46	300							
125x45	ONNA125B20	20x60	500				ONNE125B20	20x60	500	ONNT125B20	20x61	40	700
125x50										ONNT125C20	20x61	50	900
150x40	ONNA150015	15x46	400	ONNR150015	15x46	400							
150x40	ONNA150A20	20x60	400										
150x50	ONNA150B20	20x60	700				ONNE150B20	20x60	500	ONNT150B20	20x61	40	900
150x50										ONNT150C20	20x61	50	1100
175x50	ONNA175020	20x60	600							ONNT175020	20x61	50	700
175x50							ONNE175A20	20x60	600				
200x50	ONNA200020	20x60	500										
200x50	ONNA200A20	20x60	800				ONNE200A20	20x60	800	ONNT200A20	20x61	40	1000
200x50										ONNT200B25	25x61	50	1250
250x50	ONNA250A25	25x60	1200							ONNT250A25	25x61	50	1250
250x60										ONNT250025	25x76	55	1300



#### Varianti / Options



Parafili in lega leggera  
Light Metal thread guards



Parafili in poliammide  
Polyamide thread guards

Zaradi napetega dela v tekalnem delu, lažje obračanje!

Le dimensioni riportate sulle pagine del nostro catalogo sono espresse in millimetri  
All dimensional sizes shown on our catalogue are in millimeters.


**CARATTERISTICHE**

Vengono realizzate in nylon 6 alta viscosità di prima scelta.

Presentano ottima resistenza all'usura, all'abrasione ed agli urti, eccellente scorrevolezza, assoluta igienicità ed una buona resistenza ad agenti chimici inorganici, lubrificanti ed idrocarburi.

La temperatura di utilizzo va da -40°C a +80°C.

Occorre comunque notare che un utilizzo ad una temperatura superiore a +30°C riduce notevolmente le capacità di carico.

**FEATURES**

Made of nylon 6 with a high viscosity grade, these wheels have excellent resistance to wear, abrasion and impact. They have excellent flow, absolute hygiene and good resistance to inorganic chemicals, lubricants and hydrocarbons.

The operating temperature range is -40°C to +80°C.

It should be noted however that a use at a temperature higher than +30°C greatly reduces the load capacity.

**SERIE HNH**


ART. (CODE)					
080 HNH (34080H00)	80	30	40	8	300
081 HNH (34080H01)	80	30	45	8	300
100 HNH (34100H00)	100	32	40	8	330
101 HNH (34100H01)	100	32	45	8	330
125 HNH (34125H00)	125	40	45	8	370
150 HNH (34150H00)	150	35	45	10	370
151 HNH (34150H01)	150	35	50	10	370
160 HNH (34160H00)	160	45	58	12	380
200 HNH (34200H00)	200	50	58	12	500

4

**SERIE HNK**


ART. (CODE)	ART. (CODE)						
080 HNK (34080K00)	080 HNS (34080J00)	80	30	40	12	28X08	300
100 HNK (34100K00)	100 HNS (34100J00)	100	32	40	12	28X08	330
125 HNK (34125K00)	125 HNS (34125J00)	125	40	44	12	32X10	370
150 HNK (34150K00)	150 HNS (34150J00)	150	40	44	15	35X11	300
151 HNK (34150K01)	151 HNS (34150J01)	150	40	58	20	42X12	300
160 HNK (34160K00)	160 HNS (34160J00)	160	45	58	20	47X14	380
200 HNK (34200K00)	200 HNS (34200J00)	200	50	58	20	47X14	500


**CARATTERISTICHE**

Vengono realizzate in nylon 6 alta viscosità di prima scelta.

Presentano ottima resistenza all'usura, all'abrasione ed agli urti, eccellente scorrevolezza, assoluta igienicità ed una buona resistenza ad agenti chimici inorganici, lubrificanti ed idrocarburi.

La temperatura di utilizzo va da -40°C a +80°C.

Occorre comunque notare che un utilizzo ad una temperatura superiore a +30°C riduce notevolmente le capacità di carico.







**FEATURES**

Made of nylon 6 with a high viscosity grade, these wheels have excellent resistance to wear, abrasion and impact. They have excellent flow, absolute hygiene and good resistance to inorganic chemicals, lubricants and hydrocarbons.







The operating temperature range is -40°C to +80°C.

It should be noted however that a use at a temperature higher than +30°C greatly reduces the load capacity.

**SERIE ONK**


ART. (CODE)	ART. (CODE)						
100 ONK (32100K00)	100 ONS (32100J00)	100	35	40	15	35X11	450
124 ONK (32125K00)	124 ONS (32125J00)	125	35	40	15	35X11	500
125 ONK (32125K01)	125 ONS (32125J01)	125	45	58	20	47X14	650
150 ONK (32150K00)	150 ONS (32150J00)	150	45	58	20	47X14	750
200 ONK (32200K00)	200 ONS (32200J00)	200	50	58	20	47X14	900

**SERIE YNK**


ART. (CODE)	ART. (CODE)						
100 YNK (31100K00)	100 YNS (31100J00)	100	40	44	15	35X11	650
125 YNK (31125K00)	125 YNS (31125J00)	125	45	58	20	47X14	750
150 YNK (31150K00)	150 YNS (31150J00)	150	45	58	20	47X14	1000
150 YNK1 (31150K01)	150 YNS1 (31150J01)	150	70	78	20	47X14	1500
200 YNK (31200K00)	200 YNS (31200J00)	200	50	58	20	47X14	1100