



Tel: 04/257 68 20
Gsm: 040/99 00 11

RUOTE NUCLEO POLIAMMIDE RIVESTIMENTO IN POLIURETANO AD INIEZIONE

POLYAMIDE CENTRE WHEELS WITH INJECTED POLYURETHANE TREAD



Caratteristiche Ruota

Rivestimento in poliuretano ad iniezione colore blu. **ND**
colore grigio. **NF**
Struttura portante poliammide 6 ad alta densità colore nero
Movimento mozzo:
gabbia a rulli
gabbia a rulli con pista di scorrimento in acciaio.
doppi cuscinetti a sfere tenuta stagna.
Temperatura d'impiego da -15°C a +60°C.
Buona resistenza agli aggressivi chimici.
Durezza battistrada 92/98 Sh.A
Buona resistenza all'abrasione
Velocità massima di lavoro 4 km/h.
Mezzo di trazione consigliato: manuale

Wheel Features

Blue injected polyurethane tread.**ND**
Grey injected polyurethane tread.**NF**
Black high density polyamide 6 centre wheel.
Type of bearing:
roller bearing
roller bearing with steel tube.
double waterproof ball bearings.
Temperature range: from -15°C to +60°C.
Good resistance to chemicals.
Tread hardness 92/98 Sh.A
Good resistance to abrasion.
Max. working speed 4 KPH.
Operation: manual

Pavimentazioni Idonee / Floring Type



COD				COD				COD						
Icon	Icon	Icon	Icon	Icon	Icon	Icon	Icon	Icon	Icon	Icon	Icon			
80x30	ONDR080012	12x40	125	ONDT080012	12x41	29	125	80x30	ONFR080012	12x40	125			
100x30	ONDR100012	12x40	150	ONDT100012	12x41	29	150	100x30	ONFR100012	12x40	150			
100x40			ONDE100A15	15x46	175			100x40			ONFE100A15	15x46	175	
125x30	ONDR125015	15x46	200	ONDT125015	15x47	30	200	125x30	ONFR125015	15x46	200			
125x40			ONDE125A20	20x60	250			125x40			ONFE125A20	20x60	250	
150x35	ONDR150015	15x46	225	ONDT150015	15x47	30	225	150x35	ONFR150015	15x46	225			
150x45			ONDE150A20	20x60	350			150x45			ONFE150A20	20x60	350	
175x45			ONDE175020	20x60	400			175x45			ONFE175020	20x60	400	
200x50			ONDE200020	20x60	550			200x50			ONFE200020	20x60	550	
250x60								250x60						
				ONDT250025	25x76	55	800				ONFT250025	25x76	55	800

Varianti / Options



Parafili in lega leggera
Light Metal thread guards



Parafili in poliammide
Polyamide thread guards

Le dimensioni riportate sulle pagine del nostro catalogo sono espresse in millimetri
All dimensional sizes shown on our catalogue are in millimeters.