

RUOTE NUCLEO POLIAMMIDE RIVESTIMENTO IN POLIURETANO AD INIEZIONE

POLYAMIDE CENTRE WHEELS WITH INJECTED POLYURETHANE TREAD




Caratteristiche Ruota

- Rivestimento in poliuretano ad iniezione colore blu. **ND**
- colore grigio. **NF**
- Struttura portante poliammide 6 ad alta densità colore nero
- Movimento mozzo: gabbia a rulli
- gabbia a rulli con pista di scorrimento in acciaio.
- doppi cuscinetti a sfere tenuta stagna.
- Temperatura d'impiego da -15°C a +60°C.
- Buona resistenza agli aggressivi chimici.
- Durezza battistrada 92/98 Sh.A
- Buona resistenza all'abrasione
- Velocità massima di lavoro 4 km/h.
- Mezzo di trazione consigliato: manuale

Wheel features

- Blue injected polyurethane tread.**ND**
- Grey injected polyurethane tread.**NF**
- Black high density polyamide 6 centre wheel.
- Type of bearing: roller bearing
- roller bearing with steel tube.
- double waterproof ball bearings.
- Temperature range: from -15°C to +60°C.
- Good resistance to chemicals.
- Tread hardness 92/98 Sh.A
- Good resistance to abrasion.
- Max. working speed 4 KPH.
- Operation: manual

Modalità di impiego/Main features



80x30	ONDR080012	12x40	125	ONDT080012	12x41	29	125	ONDL080032B	32x12,5-34		
100x30	ONDR100012	12x40	150	ONDT100012	12x41	29	150	ONDL100032B	32x12,5-34		
100x40			ONDE100A15	15x46	175	ONDT100A15	15x47	30	175	ONDL100A35B	35x14-36
125x30	ONDR125015	15x46	200	ONDT125015	15x47	30	200	ONDL125035B	35x14-36		
125x40			ONDE125A20	20x60	250	ONDT125A20	20x61	40	250	ONDL125A47D	47x17-46
150x35	ONDR150015	15x46	225	ONDT150015	15x47	30	225	ONDL150035B	35x14-36		
150x45			ONDE150A20	20x60	350	ONDT150A20	20x61	40	350	ONDL150A47D	47x17-46
175x45			ONDE175020	20x60	400	ONDT175020	20x61	40	400	ONDL175047D	47x17-46
200x50			ONDE200020	20x60	550	ONDT200020	20x61	40	550	ONDL200047D	47x17-46
250x60						ONDT250025	25x76	55	800	ONDL250052C	52x20-65
80x30	ONFR080012	12x40	125	ONFT080012	12x41	29	125	ONFL080032B	32x12,5-34		
100x30	ONFR100012	12x40	150	ONFT100012	12x41	29	150	ONFL100032B	32x12,5-34		
100x40			ONFE100A15	15x46	175	ONFT100A15	15x47	30	175	ONFL100A35B	35x14-36
125x30	ONFR125015	15x46	200	ONFT125015	15x47	30	200	ONFL125035B	35x14-36		
125x40			ONFE125A20	20x60	250	ONFT125A20	20x61	40	250	ONFL125A47D	47x17-46
150x35	ONFR150015	15x46	225	ONFT150015	15x47	30	225	ONFL150035B	35x14-36		
150x45			ONFE150A20	20x60	350	ONFT150A20	20x61	40	350	ONFL150A47D	47x17-46
175x45			ONFE175020	20x60	400	ONFT175020	20x61	40	400	ONFL175047D	47x17-46
200x50			ONFE200020	20x60	550	ONFT200025	25x61	40	550	ONFL200047D	47x17-46
250x60						ONFT250025	25x76	55	800	ONFL250052C	52x20-65

Zaradi napetega dela v tekalnem delu, lažje obračanje!

Varianti/Options

Accessori/Accessories



Parafili in lega leggera
Light Metal thread guards



Parafili in poliammide
Polyamide thread guards