


SUPPORTI / HOUSING - L - STANDARD DUTY

Tel: 04/257 68 20
Gsm: 040/99 00 11Supporto in acciaio stampato girevole
su doppio giro di sfere.
Finitura zincata.Steel swivel housing on double ball races.
Zinc plated finishing.

girevole piastra / swivel castor



							COD	
30x15	42x42	30x30	5,2	14,5	47		3EPA0300GLO	25
36x15	42x42	30x30	5,2	14,5	50		3EPA0360GLO	25
40x18	42x42	30x30	5,2	24,5	62		3EPA0400GLO	25
50x18	42x42	30x30	5,2	24,5	66		3EPA0500GLO	35
50x18	55x55	44x44	6,2	24,5	66		3EPA0500GLO2	35
50x22	60x60	46x46	6,2	21	72		3EPA050LGLO	40
60x22	60x60	46x46	6,2	21	82		3EPA060LGLO	50
80x22	60x60	46x46	6,2	25	103		3EPA0800GLO	55

girevole piastra freno pedale anteriore / swivel castor with front brake foot lever



							COD	
50x18	42x42	30x30	5,2	24,5	66		3EPA0500GLD	35
50x18	55x55	44x44	6,2	24,5	66		3EPA0500GLD02	35

girevole foro per vite / bolt hole swivel castor



						COD		
30x15	8			14,5	47		3EPA0300QL0	25
36x15	8			14,5	50		3EPA0360QL0	25
40x18	8			24,5	60		3EPA0400QL0	25
50x18	8			24,5	66		3EPA0500QL0	35
50x22	10			21	73		3EPA050LQL0	40
60x22	10			21	82		3EPA060LQL0	50
80x22	10			25	103		3EPA0800QL0	55

girevole foro per vite freno pedale anteriore / bolt hole swivel castor with front brake foot lever



						COD		
50x18	8			24,5	66		3EPA0500QLD	35






Varianti/Options

C.6








girevole codolo filettato / *swivel threaded stem castor*



					COD	
30x15	M8x15	14,5	47		3EPA0300VLO	25
36x15	M8x15	14,5	50		3EPA0360VLO	25
40x18	M8x15	24,5	62		3EPA0400VLO	25
50x18	M8x15	24,5	66		3EPA0500VLO	35
50x18	M10x15	24,5	66		3EPA0500VLO2	35
50x22	M10x15	21	72		3EPA050LVLO	40
60x22	M10x15	21	82		3EPA060LVLO	50
80x22	M10x15	25	103		3EPA0800VLO	55







girevole codolo filettato freno pedale anteriore / *swivel threaded stem castor with front brake foot lever*



					COD	
50x18	M8x15	24,5	66		3EPA0500VLD	35
50x18	M10x15	24,5	66		3EPA0500VLD2	35

fisso piastra / *fixed castor*



						COD	
40x18	48x48	30x30	5,2		62	3EPA0400FLO	25
50x18	48x48	30x30	5,2		66	3EPA0500FLO	35
50x18	55x55	44x44	6,2		66	3EPA0500FLO2	35
50x22	60x60	46x46	6,2		72	3EPA050LFLO	40
60x22	60x60	46x46	6,2		82	3EPA060LFLO	50
80x22	60x60	46x46	6,2		103	3EPA0800FLO	55

Varianti/Options



RUOTE A STRUTTURA MONOLITICA IN POLIPROPILENE
POLYPROPYLENE WHEELS

Caratteristiche Ruota

Struttura portante in polipropilene antiurto colore nero
Movimento mozzo: alesaggio passante.
Temperatura d'impiego da +5°C a +40°C.
Buona resistenza agli aggressivi chimici.
Buona resistenza all'abrasione.

Wheel Features

Shock black resistant polypropylene wheel.
Type of bearing: plain bearing.
Temperature range: from +5°C to +40°C.
Good resistance to chemicals.
Good resistance to abrasion.



	COD		
30x15	2EPA030006	6x21	25
36x15	2EPA036006	6x21	25
40x18	2EPA040008	8x21	25
50x18	2EPA050008	8x21	35
50x22	2EPA050L08	8x28	40
60x22	2EPA060L08	8x28	50
80x22	2EPA080008	8x28	55

Varianti / Options

Le dimensioni riportate sulle pagine del nostro catalogo sono espresse in millimetri
All dimensional sizes shown on our catalogue are in millimeters.