



CARATTERISTICHE

Vengono realizzate in nylon 6 alta viscosità di prima scelta. Presentano ottima resistenza all'usura, all'abrasione ed agli urti, eccellente scorrevolezza, assoluta igienicità ed una buona resistenza ad agenti chimici inorganici, lubrificanti ed idrocarburi. La temperatura di utilizzo va da -25°C a +80°C. Occorre comunque notare che un utilizzo ad una temperatura superiore a +30°C riduce notevolmente le capacità di carico.

FEATURES

Made of nylon 6 with a high viscosity grade, these wheels have excellent resistance to wear, abrasion and impact. They have excellent flow, absolute hygiene and good resistance to inorganic chemicals, lubricants and hydrocarbons. The operating temperature range is -25°C to +80°C. It should be noted however that a use at a temperature higher than +30°C greatly reduces the load capacity.

SERIE HNH



ART. (CODE)					
080 HNH (34080H00)	80	30	40	8	300
081 HNH (34080H01)	80	30	45	8	300
100 HNH (34100H00)	100	32	40	8	330
101 HNH (34100H01)	100	32	45	8	330
125 HNH (34125H00)	125	38	45	8	370
150 HNH (34150H00)	150	35	45	10	370
151 HNH (34150H01)	150	35	50	10	370
160 HNH (34160H00)	160	45	58	12	300
200 HNH (34200H00)	200	50	58	12	500

SUPPORTI ZINCATI ZINC PLATED CASTORS



080 HNH	080 HNH	080 HNH/F	080 HNH	080 HNH/F	80	108	32	9	100X85	80X60	M12	130
100 HNH	100 HNH	100 HNH/F	100 HNH	100 HNH/F	100	127	32	9	100X85	80X60	M12	130
125 HNH	125 HNH	125 HNH/F	125 HNH	125 HNH/F	125	157	32	9	100X85	80X60	M12	130
150 HNH	150 HNH	150 HNH/F	150 HNH	150 HNH/F	150	182	32	9	100X85	80X60	M12	150
160 HNH	160 HNH	160 HNH/F	160 HNH	160 HNH/F	160	197	52	11	130X105	105X80	M12	250
200 HNH	200 HNH	200 HNH/F	200 HNH	200 HNH/F	200	240	48	11	130X105	105X80	M12	270

PO NAROČILU TUDI V INOX IZVEDBI




CARATTERISTICHE

Vengono realizzate in nylon 6 alta viscosità di prima scelta. Presentano ottima resistenza all'usura, all'abrasione ed agli urti, eccellente scorrevolezza, assoluta igienicità ed una buona resistenza ad agenti chimici inorganici, lubrificanti ed idrocarburi. La temperatura di utilizzo va da -25°C a +80°C. Occorre comunque notare che un utilizzo ad una temperatura superiore a +30°C riduce notevolmente le capacità di carico.

FEATURES

Made of nylon 6 with a high viscosity grade, these wheels have excellent resistance to wear, abrasion and impact. They have excellent flow, absolute hygiene and good resistance to inorganic chemicals, lubricants and hydrocarbons. The operating temperature range is -25°C to +80°C. It should be noted however that a use at a temperature higher than +30°C greatly reduces the load capacity.

SERIE HNK


ART. (CODE)	ART. (CODE)						
080 HNK (34080K00)	080 HNS (34080J00)	80	30	40	12	28X08	300
100 HNK (34100K00)	100 HNS (34100J00)	100	32	40	12	28X08	330
125 HNK (34125K00)	125 HNS (34125J00)	125	38	44	12	32X10	370
150 HNK (34150K00)	150 HNS (34150J00)	150	40	44	15	35X11	300
160 HNK (34160K00)	160 HNS (34160J00)	160	45	58	20	47X14	300
200 HNK (34200K00)	200 HNS (34200J00)	200	50	58	20	47X14	500

4
SUPPORTI ZINCATI
ZINC PLATED CASTORS


080 HNKF	080 HNKR	080 HNKRF	080 HNKRC	080 HNKCF	80	108	32	9	100X85	80X60	M12	130	
100 HNKF	100 HNKR	100 HNKRF	100 HNKRC	100 HNKCF	100	127	32	9	100X85	80X60	M12	130	
125 HNKF	125 HNKR	125 HNKRF	125 HNKRC	125 HNKCF	125	157	32	9	100X85	80X60	M12	130	
150 HNKF	150 HNKR	150 HNKRF	150 HNKRC	150 HNKCF	150	182	32	9	100X85	80X60	M12	150	
160 HNKF	160 HNKR	160 HNKRF	160 HNKRC	160 HNKCF	160	197	52	11	130X105	105X80	M12	250	
200 HNKF	200 HNKR	200 HNKRF	200 HNKRC	200 HNKCF	200	240	48	11	130X105	105X80	M12	270	



CARATTERISTICHE

Vengono realizzate in nylon 6 alta viscosità di prima scelta. Presentano ottima resistenza all'usura, all'abrasione ed agli urti, eccellente scorrevolezza, assoluta igienicità ed una buona resistenza ad agenti chimici inorganici, lubrificanti ed idrocarburi. La temperatura di utilizzo va da -40°C a +80°C. Occorre comunque notare che un utilizzo ad una temperatura superiore a +30°C riduce notevolmente le capacità di carico.

FEATURES

Made of nylon 6 with a high viscosity grade, these wheels have excellent resistance to wear, abrasion and impact. They have excellent flow, absolute hygiene and good resistance to inorganic chemicals, lubricants and hydrocarbons. The operating temperature range is -40°C to +80°C. It should be noted however that a use at a temperature higher than +30°C greatly reduces the load capacity.

SERIE YNK



ART. (CODE)	ART. (CODE)						
							daN
100 YNK (31100K00)	100 YNS (31100J00)	100	40	44	15	35X11	650
125 YNK (31125K00)	125 YNS (31125J00)	125	45	58	20	47X14	750
150 YNK (31150K00)	150 YNS (31150J00)	150	45	58	20	47X14	1000
150 YNK1 (31150K01)	150 YNS1 (31150J01)	150	70	78	20	47X14	1500
200 YNK (31200K00)	200 YNS (31200J00)	200	50	58	20	47X14	1100



TUBO IN METALLO
METAL TUBE

SUPPORTI ZINCATI ZINC PLATED CASTORS



									daN
100 YNKF	100 YNKR	100 YNKR/F	100	135	45	9	100X85	80X60	450
125 YNKF	125 YNKR	125 YNKR/F	125	164	59	12	135X110	105X80	700
150 YNKF	150 YNKR	150 YNKR/F	150	196	59	12	135X110	105X80	700
200 YNKF	200 YNKR	200 YNKR/F	200	243	59	12	135X110	105X80	700



CARATTERISTICHE

Vengono realizzate in nylon 6 alta viscosità di prima scelta. Presentano ottima resistenza all'usura, all'abrasione ed agli urti, eccellente scorrevolezza, assoluta igienicità ed una buona resistenza ad agenti chimici inorganici, lubrificanti ed idrocarburi. La temperatura di utilizzo va da -40°C a +80°C. Occorre comunque notare che un utilizzo ad una temperatura superiore a +30°C riduce notevolmente le capacità di carico.

FEATURES

Made of nylon 6 with a high viscosity grade, these wheels have excellent resistance to wear, abrasion and impact. They have excellent flow, absolute hygiene and good resistance to inorganic chemicals, lubricants and hydrocarbons. The operating temperature range is -40°C to +80°C. It should be noted however that a use at a temperature higher than +30°C greatly reduces the load capacity.

SERIE ONK



ART. (CODE)	ART. (CODE)						daN
100 ONK (32100K00)	100 ONS (32100J00)	100	35	40	15	35X11	450
124 ONK (32125K00)	124 ONS (32125J00)	125	35	40	15	35X11	500
125 ONK (32125K01)	125 ONS (32125J01)	125	45	58	20	47X14	650
150 ONK (32150K00)	150 ONS (32150J00)	150	45	58	20	47X14	750
200 ONK (32200K00)	200 ONS (32200J00)	200	50	58	20	47X14	900

SUPPORTI ZINCATI ZINC PLATED CASTORS



									daN
100 ONKF	100 ONKR	100 ONKR/F	100	135	45	9	100X85	80X60	450
124 ONKF	124 ONKR	124 ONKR/F	125	160	50	9	100X85	80X60	450
125 ONKF	125 ONKR	125 ONKR/F	125	164	59	12	135X110	105X80	700
150 ONKF	150 ONKR	150 ONKR/F	150	196	59	12	135X110	105X80	700
200 ONKF	200 ONKR	200 ONKR/F	200	243	59	12	135X110	105X80	700